



VA503m

VA703b

VA703m

VA702

VE720m

Panel Size	15"	17"	17"	17"	17"
Panel Technology	TN	TN	TN	TN	TN
Display Area (W x H mm)	304 x 228	338 x 270	338 x 270	338 x 270	338 x 270
Pixel Pitch (mm)	0.297	0.264	0.264	0.264	0.264
Brightness (cd/m ² , typ.)	250	280	280	300	350
Contrast Ratio (typ.)	450:1	600:1	600:1	500:1	350:1
Viewing Angle h°/v° (@10:1 / @5:1)	120/100 / 160/115	150/135 / 170/155	150/135 / 170/155	140/130 / 160/155	160/120 / 160/150
Response Time (ms, typ.)	16	8	8	8	8
Colour Support (millions of colours)	6-bit + 2-bit FRC (16.2)	6-bit + 2-bit FRC (16.2)	6-bit + 2-bit FRC (16.2)	6-bit + 2-bit FRC (16.2)	6-bit + 2-bit FRC (16.2)
True Panel (Native) Resolution	1024 x 768	1280 x 1024	1280 x 1024	1280 x 1024	1280 x 1024
Interface	Analogue (captive cable)	Analogue (captive cable)	Analogue (captive cable)	Analogue (captive cable)	Analogue
Pivot Function	-	-	-	-	-
ViewMatch® Colour Control	●	●	●	●	●
OSD and Power Lock	●	●	●	●	●
Business Audio	●	-	●	-	●
VESA® Wall Mount (mm)	75	100	100	100	75
Height Adjustment	-	-	-	-	● (100mm)
Horiz. Scan. Frequency (kHz)	30-82	30-82	30-82	30-82	30-82
Vert. Scan. Frequency (Hz)	50-85	50-85	50-85	50-85	50-85
Dimensions (W x H(min) H(max) x D mm)	344 x 348 x 147	379 x 400 x 210	379 x 400 x 210	378 x 374 x 196	386 x 404 - 504 x 221
Panel Depth (mm)	53	68	68	61	61
Net Weight (kg)	2.7	3.6	3.6	4.5	4.3
Power Consumption (W, typ.)	<23	<35	<36	<35	<42
Power Save Mode (W)	<1	<1	<1	<1	<2
Power Supply	Internal	Internal	Internal	Internal	External
Other Special Features	Ø-Touch Auto Tune, Thin Bezel: 19mm Sides, Kensington Security Port	Ø-Touch Auto Tune, Kensington Security Port, VS Wizard	Ø-Touch Auto Tune, Dual Tone Colour, Kensington Security Port, VS Wizard	Ø-Touch Auto Tune, Dual Tone Colour, Kensington Security Port, VS Wizard, Folding Base	Height Adjustment, Ø-Touch Auto Tune, Dual Tone Colour, Kensington Security Port, VS Wizard
Emission Standards	TCO'99	TCO'03	TCO'03	TCO'03	TCO'99
Power Saving	TCO, ENERGY	TCO, ENERGY, ENERGY STAR®	TCO, ENERGY, ENERGY STAR®	TCO, ENERGY, ENERGY STAR®	TCO, ENERGY, ENERGY STAR®
Available Colours	■	■	■	■	■
Regulations	ISO13406-2 Class 2	ISO13406-2 Class 2	ISO13406-2 Class 2	ISO13406-2 Class 2	ISO13406-2 Class 2

Specifications

■ Midnightgrey ■ Metallic on Black ¹ DVI cable included. ² Comprehensive software included. ³ iPod® must be purchased separately.

For further warranty information please see: www.viewsoniceurope.com/UK/Support/warranty/htm. All models feature a universal power supply, Plug&Play, Mac® support and anti-glare screen treatment. Specifications are subject to change without notice. Copyright © 2006 ViewSonic Corporation. All rights reserved. Corporate names and trademarks stated herein are the property of their respective companies. [LCD-RO-UK-12/06]



VG721m



VG730m

Panel Size	17"	17"
Panel Technology	TN	TN
Display Area (W x H mm)	338 x 270	338 x 270
Pixel Pitch (mm)	0.264	0.264
Brightness (cd/m ² , typ.)	280	280
Contrast Ratio (typ.)	600:1	600:1
Viewing Angle h°/v° (@10:1 / @5:1)	150/135 / 170/155	150/145 / 170/155
Response Time (ms, typ.)	8	8
Colour Support (millions of colours)	6-bit + 2-bit FRC (16.2)	6-bit + 2-bit FRC (16.2)
True Panel (Native) Resolution	1280 x 1024	1280 x 1024
Interface	Analogue	Analogue/digital (DVI-D)
Pivot Function	-	-
ViewMatch® Colour Control	●	●
OSD and Power Lock	●	●
Business Audio	●	●
VESA® Wall Mount (mm)	75	100
Height Adjustment	-	● (80mm)
Horiz. Scan. Frequency (kHz)	30-82	30-82
Vert. Scan. Frequency (Hz)	56-75	56-75
Dimensions (W x H(min) H(max) x D mm)	387 x 428 x 206	387 x 450 - 530 x 230
Panel Depth (mm)	67	67
Net Weight (kg)	4.5	4.9
Power Consumption (W, typ.)	<35	35
Power Save Mode (W)	<1	<1
Power Supply	Internal	Internal
Other Special Features	Ø-Touch Auto Tune, Dual Tone Colour, Thin Bezel, Kensington Security Port, Cable Management, VS Wizard	Ø-Touch Auto Tune, Dual Tone Colour, Thin Bezel, Kensington Security Port, Cable Management, VS Wizard, 360° Swivel Base
Emission Standards	TCO'03	TCO'03
Power Saving	TCO, ENERGY	TCO, ENERGY
Available Colours	■	■
Regulations	ISO13406-2 Class 2	ISO13406-2 Class 2

Specifications

■ Midnightgrey ■ Metallic on Black ¹ DVI cable included. ² Comprehensive software included. ³ iPod® must be purchased separately.

For further warranty information please see: www.viewsoniceurope.com/UK/Support/warranty/htm. All models feature a universal power supply, Plug&Play, Mac® support and anti-glare screen treatment. Specifications are subject to change without notice. Copyright © 2006 ViewSonic Corporation. All rights reserved. Corporate names and trademarks stated herein are the property of their respective companies. [LCD-RO-UK-12/06]



VA902

VA903b

VA903m

VE920m

VG921m

Panel Size	19"	19"	19"	19"	19"
Panel Technology	TN	TN	TN	TN	TN
Display Area (W x H mm)	376 x 301	376 x 301	376 x 301	376 x 301	376 x 301
Pixel Pitch (mm)	0.294	0.294	0.294	0.294	0.294
Brightness (cd/m ² , typ.)	250	300	300	280	300
Contrast Ratio (typ.)	600:1	700:1	700:1	400:1	700:1
Viewing Angle h°/v° (@10:1 / @5:1)	140/130 / 160/150	150/135 / 160/150	150/135 / 160/150	150/130 / 160/150	150/135 / 160/155
Response Time (ms, typ.)	8	8	8	8	8
Colour Support (millions of colours)	6-bit + 2-bit FRC (16.2)	6-bit + 2-bit FRC (16.2)	6-bit + 2-bit FRC (16.2)	6-bit + 2-bit FRC (16.2)	6-bit + 2-bit FRC (16.2)
True Panel (Native) Resolution	1280 x 1024	1280 x 1024	1280 x 1024	1280 x 1024	1280 x 1024
Interface	Analogue (captive cable)	Analogue (captive cable)	Analogue (captive cable)	Analogue (captive cable)	Analogue
Pivot Function	-	-	-	-	-
ViewMatch® Colour Control	●	●	●	●	●
OSD and Power Lock	●	●	●	●	●
Business Audio	-	-	●	●	●
VESA® Wall Mount (mm)	100	100	100	100	100
Height Adjustment	-	-	-	● (100mm)	-
Horiz. Scan. Frequency (kHz)	30-82	30-80	30-80	30-82	30-82
Vert. Scan. Frequency (Hz)	50-85	50-85	50-85	50-85	56-76
Dimensions (W x H(min) H(max) x D mm)	414 x 407 x 219	416 x 429 x 210	416 x 429 x 210	423 x 434 – 534 x 221	426 x 457 x 205
Panel Depth (mm)	61	68	68	52	64
Net Weight (kg)	5.4	4.6	4.6	5.2	5.2
Power Consumption (W, typ.)	35	<35	<35	35	39
Power Save Mode (W)	<1	<1	<1	<1	<1
Power Supply	Internal	Internal	Internal	Internal	Internal
Other Special Features	Kensington Security Port, Cable Management, VS Wizard Thin Bezel, Folding Base	Kensington Security Port, Cable Management, VS Wizard, Thin Bezel	Kensington Security Port, Cable Management, VS Wizard, Dual Tone Colour	Kensington Security Port, Cable Management, VS Wizard, Thin Bezel	Ø-Touch Auto Tune, Kensington Security Port, Cable Management, VS Wizard, Thin Bezel
Emission Standards	TCO'03	TCO'03	TCO'03	TCO'03	TCO'03
Power Saving	TCO, ENERGY, ENERGY STAR®	TCO, ENERGY, ENERGY STAR®	TCO, ENERGY STAR®	TCO, ENERGY STAR®	TCO, ENERGY, ENERGY STAR®
Available Colours	■	■	■	■	■
Regulations	ISO13406-2 Class 2	ISO13406-2 Class 2	ISO13406-2 Class 2	ISO13406-2 Class 2	ISO13406-2 Class 2

Specifications

■ Midnightgrey ■ Metallic on Black ¹ DVI cable included. ² Comprehensive software included. ³ iPod® must be purchased separately.

For further warranty information please see: www.viewsoniceurope.com/UK/Support/warranty.htm. All models feature a universal power supply, Plug&Play, Mac® support and anti-glare screen treatment. Specifications are subject to change without notice. Copyright © 2006 ViewSonic Corporation. All rights reserved. Corporate names and trademarks stated herein are the property of their respective companies. [LCD-RO-UK-12/06]



VG930m



VX912-4



VX922



VP930



VA1912w-2

Panel Size	19"	19"	19"	19"	19" Wide (16:10 a/r)
Panel Technology	TN	TN	TN	MVA	TN
Display Area (W x H mm)	376 x 301	376 x 301	376 x 301	376 x 301	410 x 256
Pixel Pitch (mm)	0.294	0.294	0.294	0.294	0.285
Brightness (cd/m ² , typ.)	280	300	270	300	300
Contrast Ratio (typ.)	600:1	700:1	650:1	1300:1	500:1
Viewing Angle h°/v° (@10:1 / @5:1)	150/135 / 160/155	150/135 / 170/155	150/135 / 160/160	178/178 / 178/178	150/130 / 160/150
Response Time (ms, typ.)	8	5	2 (Grey to Grey)	8 (Grey to Grey)	8
Colour Support (millions of colours)	6-bit + 2-bit FRC (16.2)	6-bit + 2-bit FRC (16.2)	6-bit + 2-bit FRC (16.2)	8-bit (16.7)	6-bit + 2-bit FRC (16.2)
True Panel (Native) Resolution	1280 x 1024	1280 x 1024	1280 x 1024	1280 x 1024	1440 x 900
Interface	Analogue/digital (DVI-D)	Analogue/digital (DVI-D) ¹	Analogue/digital (DVI-D) ¹	2 x Analogue/digital (DVI-D) ¹	Analogue
Pivot Function	-	-	-	● ²	-
ViewMatch [®] Colour Control	●	●	●	●	●
OSD and Power Lock	●	●	●	●	●
Business Audio	●	●	-	-	●
VESA [®] Wall Mount (mm)	100	100	100	100	75
Height Adjustment	● (80mm)	-	-	● (135mm)	-
Horiz. Scan. Frequency (kHz)	24-82	30-82	30-82	24-82	30-82
Vert. Scan. Frequency (Hz)	50-75	50-85	50-75	50-85	50-85
Dimensions (W x H(min) H(max) x D mm)	428 x 457 – 537 x 230	431 x 468 x 201	431 x 468 x 201	412 x 356 – 491 x 289	451 x 391 x 197
Panel Depth (mm)	68	66	66	61	52
Net Weight (kg)	6.0	6.7	6.7	6.8	4.5
Power Consumption (W, typ.)	35	<35	35	38	32
Power Save Mode (W)	<1	<1	<1	<1	<1
Power Supply	Internal	Internal	Internal	Internal	Internal
Other Special Features	Ø-Touch Auto Tune, Kensington Security Port, Cable Management, VS Wizard, Thin Bezel, 360° Swivel Base	Ø-Touch Auto Tune, Kensington Security Port, VS Wizard	Ø-Touch Auto Tune, Kensington Security Port, VS Wizard	Ø-Touch Auto Tune, Kensington Security Port, Bezel only 1.7cm, VS Wizard, Main Power Switch, 270° Swivel, PerfectSuite	Ø-Touch Auto Tune, Kensington Security Port, VS Wizard, MS Vista ready, Wide Format
Emission Standards	TCO'03	TCO'99	TCO'99	TCO'03	TCO'99
Power Saving	TCO, ENERGY, ENERGY STAR [®]	TCO, ENERGY	TCO, ENERGY	Energy 2000, ENERGY STAR [®]	Energy 2000, ENERGY STAR [®]
Available Colours	■	■	■	■	■
Regulations	ISO13406-2 Class 2	ISO13406-2 Class 2	ISO13406-2 Class 2	ISO13406-2 Class 2	ISO13406-2 Class 2

■ Midnightgrey ■ Metallic on Black ¹ DVI cable included. ² Comprehensive software included. ³ iPod[®] must be purchased separately.

For further warranty information please see: www.viewsoniceurope.com/UK/Support/warranty.htm. All models feature a universal power supply, Plug&Play, Mac[®] support and anti-glare screen treatment. Specifications are subject to change without notice. Copyright © 2006 ViewSonic Corporation. All rights reserved. Corporate names and trademarks stated herein are the property of their respective companies. [LCD-RO-UK-12/06]

Specifications



VG1921wm



VG1930wm



VX1935wm



VX1945wm

Panel Size	19" Wide (16:10 a/r)	19" Wide (16:10 a/r)	19" Wide (16:10 a/r)	19" Wide (16:10 a/r)
Panel Technology	TN	TN	TN	TN
Display Area (W x H mm)	410 x 256	410 x 256	410 x 256	410 x 256
Pixel Pitch (mm)	0.285	0.285	0.285	0.285
Brightness (cd/m ² , typ.)	300	300	300	300
Contrast Ratio (typ.)	700:1	700:1	700:1	700:1
Viewing Angle h°/v° (@10:1 / @5:1)	160/140 / 160/160	160/160 / 170/170	130/120 / 150/140	140/140 / 160/160
Response Time (ms, typ.)	5	5	5	5
Colour Support (millions of colours)	6-bit + 2-bit FRC (16.2)	6-bit + 2-bit FRC (16.2)	6-bit + 2-bit FRC (16.2)	6-bit + 2-bit FRC (16.2)
True Panel (Native) Resolution	1440 x 900	1440 x 900	1440 x 900	1440 x 900
Interface	Analogue	Analogue/digital (DVI-D) ¹	Analogue/digital (DVI-D) ¹	Analogue/digital (DVI-D) ¹
Pivot Function	-	-	-	-
ViewMatch [®] Colour Control	●	●	●	●
OSD and Power Lock	●	●	●	●
Business Audio	●	●	●	● (& subwoofer)
VESA [®] Wall Mount (mm)	75	75	100	100
Height Adjustment	-	● (80mm)	-	-
Horiz. Scan. Frequency (kHz)	30-82	24-82	30-82	30-82
Vert. Scan. Frequency (Hz)	56-75	50-75	50-85	50-85
Dimensions (W x H(min) H(max) x D mm)	460 x 416 x 206	460 x 434 - 514 x 230	450 x 434 x 210	450 x 449 x 212
Panel Depth (mm)	62	61	66	66
Net Weight (kg)	5.0	5.4	5.6	5.7
Power Consumption (W, typ.)	35	35	35	59
Power Save Mode (W)	<1	<1	<1	<1
Power Supply	Internal	Internal	Internal	Internal
Other Special Features	Ø-Touch Auto Tune, Kensington Security Port, VS Wizard, Stereo Audio, Wide Format	Ø-Touch Auto Tune, Kensington Security Port, VS Wizard, 360° Swivel Base, Stereo Audio, Wide Format, Height Adjustment	Ø-Touch Auto Tune, Kensington Security Port, VS Wizard, Wide Format	iPod Docking Station (Made for iPod certified), Microphone, 8-in-1 Card Reader, USB 2.0 1up/4down, Wide Format
Emission Standards	TCO'03	TCO'03	MPR II	MPR II
Power Saving	ENERGY	ENERGY	ENERGY	ENERGY
Available Colours	■	■	■	■
Regulations	ISO13406-2 Class 2	ISO13406-2 Class 2	ISO13406-2 Class 2	ISO13406-2 Class 2

■ Midnightgrey ■ Metallic on Black ¹ DVI cable included. ² Comprehensive software included. ³ iPod[®] must be purchased separately.

For further warranty information please see: www.viewsoniceurope.com/UK/Support/warranty/htm. All models feature a universal power supply, Plug&Play, Mac[®] support and anti-glare screen treatment. Specifications are subject to change without notice. Copyright © 2006 ViewSonic Corporation. All rights reserved. Corporate names and trademarks stated herein are the property of their respective companies. [LCD-RO-UK-12/06]

Specifications



VA2012w-2



VG2021wm



VX2025wm



VG2021m-2



VP2030b

	VA2012w-2	VG2021wm	VX2025wm	VG2021m-2	VP2030b
Panel Size	20" Wide (16:10 a/r)	20" Wide (16:10 a/r)	20.1" Wide (16:10 a/r)	20.1"	20.1"
Panel Technology	TN	TN	MVA	TN	MVA
Display Area (W x H mm)	433 x 271	433 x 271	433 x 271	408 x 306	408 x 306
Pixel Pitch (mm)	0.258	0.258	0.258	0.29	0.255
Brightness (cd/m ² , typ.)	300	300	300	300	300
Contrast Ratio (typ.)	600:1	800:1	800:1	500:1	1000:1
Viewing Angle h°/v° (@10:1 / @5:1)	140/125 / 160/145	160/160 / 170/170	176/176 / 176/176	150/130 / 170/155	170/170 / 170/170
Response Time (ms, typ.)	8	5	8 (Grey to Grey)	8	8 (Grey to Grey)
Colour Support (millions of colours)	6-bit + 2-bit FRC (16.2)	6-bit + 2-bit FRC (16.2)	8-bit (16.7)	6-bit + 2-bit FRC (16.2)	8-bit (16.7)
True Panel (Native) Resolution	1680 x 1050	1680 x 1050	1680 x 1050	1400 x 1050	1600 x 1200
Interface	Analogue	Analogue	Analogue/digital (DVI-D) ¹	Analogue	Analogue/digital (DVI-I) ¹
Pivot Function	-	-	-	-	● ²
ViewMatch [®] Colour Control	●	●	●	●	●
OSD and Power Lock	●	●	●	●	●
Business Audio	●	●	●	●	-
VESA [®] Wall Mount (mm)	100	100	100	75	100
Height Adjustment	-	-	-	-	● (135mm)
Horiz. Scan. Frequency (kHz)	30-94	24-92	30-82	30-82	30-92
Vert. Scan. Frequency (Hz)	50-75	50-85	50-75	56-76	50-85
Dimensions (W x H(min) H(max) x D mm)	479 x 423 x 216	493 x 455 x 205	485 x 441 x 201	458 x 465 x 205	468 x 403 - 538 x 315
Panel Depth (mm)	63	71	67	61	66
Net Weight (kg)	5.5	6.8	6.3	6.2	9.0
Power Consumption (W, typ.)	47	43	35	<50	52
Power Save Mode (W)	<2	<1	<1	<1	<3
Power Supply	Internal	Internal	Internal	Internal	Internal
Other Special Features	Ø-Touch Auto Tune, Kensington Security Port, VS Wizard, Wide Format	Ø-Touch Auto Tune, Kensington Security Port, VS Wizard, Wide Format	Ø-Touch Auto Tune, Kensington Security Port, VS Wizard, MS Vista ready, Invisible Audio, Wide Format	Ø-Touch Auto Tune, Kensington Security Port, VS Wizard	Ø-Touch Auto Tune, Kensington Security Port, VS Wizard, Main Power Switch, USB 2.0 1up/4down, Bezel only 1.9cm, 270° Swivel, PerfectSuite
Emission Standards	TCO'99	TCO'03	TCO'99	TCO'03	TCO'99
Power Saving	Energy 2000, ENERGY STAR [®]	ENERGY	Energy 2000, ENERGY STAR [®]	Energy 2000, ENERGY STAR [®]	Energy 2000, ENERGY STAR [®]
Available Colours	■	■	■	■	■
Regulations	ISO13406-2 Class 2	ISO13406-2 Class 2	ISO13406-2 Class 2	ISO13406-2 Class 2	ISO13406-2 Class 2

Specifications

■ Midnightgrey ■ Metallic on Black ¹ DVI cable included. ² Comprehensive software included. ³ iPod[®] must be purchased separately.

For further warranty information please see: www.viewsoniceurope.com/UK/Support/warranty/htm. All models feature a universal power supply, Plug&Play, Mac[®] support and anti-glare screen treatment. Specifications are subject to change without notice. Copyright © 2006 ViewSonic Corporation. All rights reserved. Corporate names and trademarks stated herein are the property of their respective companies. [LCD-RO-UK-12/06]



VP2130b



VG2230wm



VX2235wm



VX2245wm



VP2330wb

	VP2130b	VG2230wm	VX2235wm	VX2245wm	VP2330wb
Panel Size	21.3"	22" Wide (16:10 a/r)	22" Wide (16:10 a/r)	22" Wide (16:10 a/r)	23" Wide (16:10 a/r)
Panel Technology	PVA	TN	TN	TN	MVA
Display Area (W x H mm)	432 x 324	474 x 296	474 x 296	474 x 296	495 x 310
Pixel Pitch (mm)	0.27	0.282	0.282	0.282	0.258
Brightness (cd/m ² , typ.)	300	280	280	280	250
Contrast Ratio (typ.)	1000:1	700:1	700:1	700:1	800:1
Viewing Angle h°/v° (@10:1 / @5:1)	178/178 / 178/178	150/140 / 170/160	150/140 / 170/160	150/140 / 170/160	170/170 / 170/170
Response Time (ms, typ.)	8 (Grey to Grey)	5	5	5	8 (Grey to Grey)
Colour Support (millions of colours)	8-bit (16.7)	6-bit + 2-bit FRC (16.2)	6-bit + 2-bit FRC (16.2)	6-bit + 2-bit FRC (16.2)	8-bit (16.7)
True Panel (Native) Resolution	1600 x 1200	1680 x 1050	1680 x 1050	1680 x 1050	1920 x 1200
Interface	Analogue/digital (DVI-I) ¹	Analogue/digital (DVI-D) ¹	Analogue/digital (DVI-D) ¹	Analogue/digital (DVI-D) ¹	Analogue/digital (DVI-I) ¹
Pivot Function	● ²	-	-	-	● ²
ViewMatch [®] Colour Control	●	●	●	●	●
OSD and Power Lock	●	●	●	●	●
Business Audio	-	●	●	● (& subwoofer)	-
VESA [®] Wall Mount (mm)	100	100	100	100	100
Height Adjustment	● (135mm)	● (135mm)	-	-	● (135mm)
Horiz. Scan. Frequency (kHz)	24-92	24-82	30-82	30-82	24-96
Vert. Scan. Frequency (Hz)	50-85	50-85	50-85	50-85	50-85
Dimensions (W x H(min) H(max) x D mm)	468 x 404 – 539 x 315	519 x 436 – 571 x 250	524 x 482 x 244	524 x 493 x 212	542 x 404 – 539 x 295
Panel Depth (mm)	63	60	58	62	110
Net Weight (kg)	9.2	6.6	6.0	6.2	7.8
Power Consumption (W, typ.)	55	43	48	62	83
Power Save Mode (W)	<3	<1	<1	<1	<4
Power Supply	Internal	Internal	Internal	Internal	External
Other Special Features	Ø-Touch Auto Tune, Kensington Security Port, VS Wizard, Main Power Switch, USB 2.0 1up/4down, Bezel only 1.7cm, 270° Swivel, PerfectSuite	Ø-Touch Auto Tune, Kensington Security Port, VS Wizard, Wide Format, 360° Swivel Base	Ø-Touch Auto Tune, Kensington Security Port, VS Wizard, Wide Format	iPod docking station (Made for iPod certified), 8-in-1 card reader, microphone, USB 2.0 1up/4down, Wide Format	Ø-Touch Auto Tune, Kensington Security Port, VS Wizard, USB 2.0 1up/4down, Bezel only 2.2cm, 270° Swivel, PerfectSuite
Emission Standards	TCO'99	TCO'03	MPR II	MPR II	TCO'99
Power Saving	Energy 2000, ENERGY STAR [®]	ENERGY	ENERGY	ENERGY	Energy 2000, ENERGY STAR [®]
Available Colours	■	■	■	■	■
Regulations	ISO13406-2 Class 2	ISO13406-2 Class 2	ISO13406-2 Class 2	ISO13406-2 Class 2	ISO13406-2 Class 2

Specifications

■ Midnightgrey ■ Metallic on Black ¹ DVI cable included. ² Comprehensive software included. ³ iPod[®] must be purchased separately.

For further warranty information please see: www.viewsoniceurope.com/UK/Support/warranty.htm. All models feature a universal power supply, Plug&Play, Mac[®] support and anti-glare screen treatment. Specifications are subject to change without notice. Copyright © 2006 ViewSonic Corporation. All rights reserved. Corporate names and trademarks stated herein are the property of their respective companies. [LCD-RO-UK-12/06]